

## Product information

- Indoor use only
- Dimmable - When used with dimmable bulbs
- Replacement bulbs should be the same type and rating, available from John Lewis Partners or other established brands
- Clean the fitting with a soft dry cloth. Do not use abrasive chemical cleaners as this will damage the finish

## Aftercare and Troubleshooting

### You've switched on the light, but it's not working:

1. Check your power supply is switched on
2. Turn off the light and check that the bulb is inserted correctly
3. Check the bulb is still in working order

If there are technical issues with this product that you can't solve, please contact your nearest John Lewis & Partners shop or call Technical Support on 03301 230106.

## Specification

Max power: 2 x 10W  
Recommended bulb:  
2 x 10W E27 GLS LED bulb for maximum brightness.  
Lower wattages are also suitable.  
Rated input: 220 –240V, 50Hz  
Bulbs not included  
IP rating: 20  
Weight: 1.45kg

## 5-year guarantee


At John Lewis & Partners we test every light to high quality standards. That means we can offer you a 5-year guarantee.

## Recycling

This symbol  indicates that this product should not be treated as normal household waste and it should be recycled. John Lewis & Partners do not operate instore take back, but as members of the Distributor Take Back scheme have funded the development and upgrade of recycling facilities across the UK. Please take it to your nearest collection facility or for further details contact your local council or visit [www.recycle-more.co.uk](http://www.recycle-more.co.uk).



# MILLHOUSE 2 LIGHT PENDANT USER GUIDE



John Lewis plc  
SW1V 2QQ  
[johnlewis.com](http://johnlewis.com)

Made in China



05/01/2024

Please retain these instructions for future reference.



Product Code:  
70140818




## Getting started

Thank you for purchasing this John Lewis & Partners product. For your safety, and to make sure everything is working properly, please read the instructions carefully before use.

## Warnings

This is a Class II product and must NOT be earthed. It is recommended that this fitting is installed by a qualified electrician. Install in accordance with the IEE Wiring regulations and the Building Regulations. To prevent electrocution switch off at mains supply before installing or maintaining this fitting. Ensure other persons cannot restore the electrical supply without your knowledge. If you are in any doubt, please consult a qualified electrician. This light fitting should be connected to a 5 amp fused circuit. If replacing an existing fitting, make a note of the connections. Always use the correct type and wattage bulb. Never exceed the wattage stated. Dispose of used bulbs carefully. This product is suitable for installation on surfaces with normal flammability e.g. wood, plasterboard, masonry. It is not suitable for use on highly flammable surfaces (e.g. polystyrene, textiles). For your safety, always switch off the supply and allow the fitting to cool down before changing lightbulbs, cleaning, removing shades or adjusting the light's position.

## Parts list

Description	Image	Quantity
Light fitting and x 2 shade rings (fitted)		x 1
Shades		x 2
Hex key		x 1
Wall plugs		x 2
Screws		x 2

## Product assembly

### Step 1


Carefully unpack the carton, making sure all the parts are present before assembly. Before removing the existing fitting, carefully note the position of each set of wires.

### Step 2

Attach the stem by screwing the stem into the threaded part of the body (A). Pull any excess cable through from the top of the ceiling cup. Ensure the stem is twisted 6 times anticlockwise before fixing into place to avoid twisting the internal cable. Tighten to secure.


### Step 3

The height of the product can be adjusted by loosening the grub screw (C) then twisting the collar (B) on the stem and withdrawing the inner stem to the appropriate height. When reducing the height make sure to pull any excess cable through the ceiling cover. Re-tighten the collar by hand and use the grub screw (C) and hex key (D) to secure.




### Step 4

Remove the backplate from the light fitting by undoing the two finials (E) from the ceiling cover. Using the backplate as a template, mark the position of the mounting holes. Drill holes and fit supplied wall plugs (F). Ensure there is a joist at the point of fixing to support the weight of the product. Take care to avoid damaging any concealed wiring and pipes. Feed the incoming mains supply cable through the entry hole. Fix the backplate to the ceiling using supplied screws (G).



### Step 5

Having identified the household wiring from your existing light fitting, connect to the connection block inside the product as shown. Check that: You have correctly identified the house wires. The connections are tight. No loose strands have been left out of the connection block. The lid is fitted back onto the terminal block case.



### Step 6

Re attach the product to the backplate using the two finials removed earlier and tighten to secure. Take care not to trap any wiring.

### Step 7

Remove shade rings (H) from threaded body, attach the shades (I) and replace the shade rings. Tighten with light pressure. Fit the recommended bulbs. Your light is now ready to use.

