

VORONOI III

5W | 250 lm | 2200K

VORN-III-5W-2200K-E27-T-02

Voronoi III 5W 2200K E27 Tinted LED Bulb, V.2


tala®

The Voronoi III bulb by Tala is noted for its oversized form and dramatic light output. The exposed internal filament mirrors the Fibonacci sequence, wrapping around a central glass column, and the unique glass shape catches the eye and the imagination. Fitted with E27 base cap.



PHYSICAL

Bulb diameter:	195mm
Bulb length:	344mm
Glass shape:	A195*
Base:	E27
Materials:	Glass & nickel
Glass finish:	Tinted
Weight:	355g
Max. working temp.:	-5°C to 40°C
IP rating:	IP54




ELECTRICAL

Power:	5W
Current:	0.02A
Voltage:	220-240V~
Frequency:	50/60Hz
Power factor:	0.9
Efficiency:	50 lm/W
Lifetime:	15,000 hrs

ILLUMINATION

CCT:	2200K
Lumens:	250 lm
Incandescent equiv.:	25W
Flicker:	<5%
Beam angle:	360°
Light source:	LED
CRI:	95Ra
R9:	80
TM30 - Rg	100
TM30 - Rf	94

IES/LDT photometry files and product photography available on request



DIMMING

Dimmable 0-100%
Recommended dimmer: Varilight V-Pro
(For a full list of recommended and compatible dimmers see website)

Tala Energy Ltd. 25b Vyner Street,
London, E2 9DG, United Kingdom

Tala Europe B.V. Bertus Aafjeshove 40
Nieuwegein 3437 JN

LOGISTICAL

Unit Packaging	Outer Carton
PC/Ctn: 1	PC/Ctn: 2
Gross weight: 580	Gross weight: TBC
L 250 x W 250 x H 400mm	L TBC x W TBC x H TBCcm

tala.co.uk | hello@tala.co.uk | +44 7700 170343

WARRANTY

2 years

EAN

5060400159666

Specification subject to change without notice. Refer to our website for the most recent product documentation. Tala designs in the EU/UK are protected by registered and or unregistered design rights