Product information	Partners or other established bra	e same type and rating, available from John Lewis	JOHN LEWIS & PARTNERS	Baldwin 3 light sp User guide	OTLIGHT BAR
Aftercare and Troubleshooting	You've switched on the light, but in 1. Check your power supply is switt 2. Turn off the light and check that 3. Check the bulb is still in working	ched on the bulb is inserted correctly			
	If there are technical issues with this product that you can't solve, please contact your nearest John Lewis & Partners shop or call Technical Support on 03301 230106.				
Specification	Max power: 3 x 7W Recommended bulb: 7W LED GU10 bulb for maximum brightness. Lower wattages are also suitable. Rated input: 220 –240V, 50Hz Bulbs not included IP rating: 20 Weight: 1.16kg	Fitting a GU10 bulb Fit bulb pins into round holes. Then push and twist clockwise to lock. To remove bulbs turn one quarter turn anticlockwise and gently pull out.			
5-year guarantee	At John Lewis & Partners we test e That means we can offer you a 5-ye				
Recycling	household waste and it should be r operate instore take back, but as m scheme have funded the developm	roduct should not be treated as normal recycled. John Lewis & Partners do not embers of the Distributor Take Back ent and upgrade of recycling facilities ir nearest collection facility or for further • visit www.recycle-more.co.uk.			
John Lewis plc			(5 YEARS		

John Lewis plc SW1V 2QQ johnlewis.com



19/05/2025

Made in China

Please retain these instructions for future reference.

Product Code: 10522303 10522308 10522109

Getting started	Thank you for purchasing this John Lewis & Partners product. For your safety, and to make sure everything is working properly, please read the instructions carefully before use.
Warnings	This is a Class II product and must NOT be earthed. It is recommended that this fitting is installed by a qualified electrician. Install in accordance with the IEE Wiring regulations and the Building Regulations. To prevent electrocution switch off at mains supply before installing or maintaining this fitting. Ensure other persons cannot restore the electrical supply without your knowledge If you are in any doubt, please consult a qualified electrician. This light fitting should be connected to a 5 amp fused circuit. If replacing an existing fitting, make a note of the connections. Always use the correct type and wattage bulb. Never exceed the wattage stated. Dispose of used bulbs carefully. This product is suitable for installation on surfaces with normal flammability e.g. wood, plasterboard, masonry. It is not suitable for use on highly flammable surfaces (e.g. polystyrene, textiles). For your safety, always switch off the supply and allow the fitting to cool down before changing lightbulbs, cleaning or adjusting heads.

Description	Image	Quantity
Light fitting with x 3 shade rings (fitted)		x 1
Shades		× 3
Knuckle adjustment tool		x 1
Metal washers	00	x 2
Wall plugs		x 2
Screws	( <del>þuunnunne)</del> ( <del>þuunnune)</del>	x 2

## Product assembly

#### Step 1

Carefully unpack the carton, making sure all the parts are present before assembly. Before removing the existing fitting, carefully note the position of each set of wires.

### Step 2

Remove the fixing bracket (A) from the product by unscrewing the two finials (B) and retain for reuse.

Ensure there is a solid mounting surface to support the weight of the light fitting. Using the fixing bracket as a template, mark the position of the mounting holes. Drill holes and fit supplied wall plugs (C) (suitable for masonary only).

Take care to avoid damaging any concealed wiring and pipes. Fix the bracket to the ceiling using supplied metal washers and screws (D).

### Step 3

Having identified the household wiring from your existing light fitting, connect to the connection block (E) inside the product in the following way. Check that: You have correctly identified the house wires. The connections are tight.

No loose strands have been left out of the connection block. The lid is closed securely over the teminal block.

#### Step 4

Re-attach the product to the fixing bracket using the two finials removed in step 2 and tighten to secure. Take care not to trap any wiring.

# Step 5

To fit the shades (F), first remove the shade rings (G) from the threaded lampholders. Place the shades over the lampholders and refit the shade rings. Secure in place.

### Step 6

Fit the recommended bulbs (H) as per the details overleaf.

# Step 7

Your light is now ready for use.

# Note:

The angle of the heads can be adjusted. Using the supplied tool (I), just loosen the knuckles on the arms, adjust to the appropriate angle and re-tighten the knuckles.





