

Type	Technical Code	Commercial Code	Code
Hoods	K21BNLFZXE800	KV120PROXT	F005134
<b>General information</b>			
Stato	UnderReview	Life Cycle	Y2 - On Management
Product family	HOODS WALLMOUNT 60-120 CM	Aesthetical line	PROFESSIONAL
Brand	BERTAZZONI	Private Label	BERTAZZONI
Make or Buy Flag	8ought	Type of production	CBU
Type of installation	FREE STANDING	Factory	Guastalla
Technical code	K21BNLFZXE800	Predecessor Code	
Commercial description	120cm Angled Wallmounted Hood		Technical code of derivation
Short Description IT	120 cm cappa a parete	Short Description FR	Hotte murale d'angle 120cm
Short Description EN	120 cm wallmount hood	Short Description US	120cm Angled Wallmounted Hood
EAN Required	YES	Ean code	8059304886720
Commercial code	KV120PROXT	Second commercial code	
Market	EUROPE	Customer	GENERICO
Years of warranty		Approvals	CE
Notes		Changes notes	
Energy Label			
Energy Label Required	YES	Annual energy consumption - AEEhood (kWh/annum)	48.0
Fluid dynamic efficiency class	A	Fluid dynamic efficiency	31.3
Energy efficiency class	A		
Measured air pressure at best efficiency point - P <sub>bep</sub> (Pa)	389	Minimum air flow in normal use (m <sup>3</sup> /h)	322.0
Maximum air flow in normal use (Intensive / Boost Excluded) (m <sup>3</sup> /h)	603	Air flow at Intensive/Boost Setting - (m <sup>3</sup> /h)	740.0
Lighting efficiency class	E	Light efficiency	16.3
Power consumption in standby mode - P <sub>s</sub> (W)	0.48	Power consumption off Mode - P <sub>o</sub> (W)	
Grease filtering efficiency - GFEhood (%)	32.5	Grease filtering efficiency class	G
Energy Label Country	UE + UK		
<b>Technical Data</b>			
Supply voltage [V]/Supply frequency [Hz]	220-240 V, 50/60 HZ	Absorbed power [W]	255
Absorbed current [A]	1	Plug type	NO
Minimum Cable length (m)	1.3	Minimum Cable length (in)	51"
Output air extraction (m <sup>3</sup> /h)	740		
Max extraction power (CFM)	NON APPLICABLE	Max extraction power (SONES)	
Sound level maximum speed (dba)	61	Sound level maximum speed (Sones)	
Sound level maximum speed/Boost (dba)	66	Sound level maximum speed/Booster (Sones)	
Sound level minimum speed (dba)	47	Sound level minimum speed (Sones)	
Microwave magnetron power	NO	Grill max power (W)	NO
Suction type	SUCTION AND FILTER		
<b>Dimensions &amp; Weights</b>			
Size	120	Height PF (in)	
Height PF (mm)	280	Width PF (in)	
Width PF (mm)	1198	Depth PF (in)	
Depth PF (mm)	500	Depth with handle (in)	
Depth with handle (mm)		Depth with open door (in)	
Depth with open door (mm)			
Built-in hole height (mm)		Built-in hole height (in)	
Built-in hole width (mm)		Built-in hole width (in)	
Built-in hole depth (mm)		Built-in hole depth (in)	
Chimney height (mm)	550-800	Chimney height (in)	
Package type	STANDARD PACKING		
Package height (mm)	630	Package height (in)	
Package width (mm)	1260	Package width (in)	
Package depth (mm)	470	Package depth (in)	
Hood distance from worktop (mm)	650	Hood distance from worktop (in)	
Net weight (kg)	27	Gross weight (Lb)	0.0
Gross weight (kg)	39.0	Net weight (Lb)	
<b>Aesthetics</b>			
Badge	SERIGRAPHY	Location of fascia	FRONT
Handle type	NO	Knob type	NO
<b>User interface</b>			
Type of control device	ELECTRIC WITH LED		
Grill power levels	NO	Microwave number of power levels	NO
<b>Product characteristics</b>			
Hood version	WALL MOUNT	Duct cover	INCLUDED
Duct size diameter (in)		Max height of installation (ft)	
Motor	1	Speed	3 + BOOSTER
Filter type	BAFFLE STAINLESS STEEL	Filter cleaning	WASHABLE
Type and number of lights	LED BAR		
Filters number	4	Hood Special features	24H FUNCTION;TIMER
Perimental aspiration	NO	Digital airflow control	NO
<b>Microwave</b>			
Microwave type	NO	Microwave functions	NO
Microwave special features	NO	Turntable	NO
Cavity material	NO	Light	NO
Guides type	NO		
Gross volume	0	Net volume	0
Microwave grill tray	NO	Microwave gasket	NO
<b>Safety Devices</b>			
Locked controls	NO	Saturation alarm	YES
<b>Documentation</b>			
Booklet languages	DANISH;DUTCH;ENGLISH;FRENCH;ITALIAN;SPANISH;SWEDISH	Warranty certificate	NO
<b>Miscellaneous</b>			
Marketing remarks			