

Type	Technical Code	Commercial Code	Code		
Hoods	KF1BNLF2XE.50	KT110P1XV	F006026		
General Information					
Stato	UnderReview	Life Cycle	Y2 - On Management		
Product family	HOODS WALLMOUNT 60-120 CM	Aesthetical line	NEUTRAL	Colour leading code	STAINLESS STEEL
Brand	BERTIAZZONI	Private Label	BERTIAZZONI		
Make or Buy Flag	Bought	Type of production	CBU		
Type of installation	FREE STANDING	Factory	Guastalla		
Technical code	KF1BNLF2XE.50	Predecessor Code	KA1BNLF2XE.50	Technical code of derivation	
Commercial description	110cm Wallmount Hood XV				
Short Description IT	110cm Wallmount Hood XV	Short Description FR	110cm Wallmount Hood XV		
Short Description EN	110cm Wallmount Hood XV	Short Description US	110cm Wallmount Hood XV		
EAN Required	YES	Ean code	8057971107087		
Commercial code	KT110P1XV	Second commercial code			
Market	EUROPE;GREAT BRITAIN	Customer	GENERIC0		
Years of warranty		Approvals	CE;UKCA	Approval code	
Notes		Changes notes			
Energy Label					
Energy Label Required	YES	Annual energy consumption - AEEhood (kWh/annum)	73.1		
Fluid dynamic efficiency class	B	Fluid dynamic efficiency	25.6		
Energy efficiency class	B				
Measured air pressure at best efficiency point - Pbeq (Pa)	395	Minimum air flow in normal use (m³/h)	290.0		
Maximum air flow in normal use (Intensive / Boost Excluded) (m³/h)	590	Air flow at Intensive/Boost Setting - (m³/h)	710.0		
Lighting efficiency class	A	Light efficiency	109		
Power consuption in standby mode - Ps (W)	0	Power consuption off Mode - Po (W)	0.49		
Grease filtering efficiency - GFEhood (%)	75.1	Grease filtering efficiency class	C		
Energy Label Country	UE + UK				
Technical Data					
Supply voltage [V]/Supply frequency [Hz]	220-240 V , 50/60 HZ	Absorbed power [W]	272		
Absorbed current [A]	0	Plug type	NO		
Minimum Cable length (m)	1.5	Minimum Cable length (in)	59"		
Output air extraction (m³/h)	710				
Max extraction power (CFM)	NON APPLICABLE	Max extraction power (SONES)			
Sound level maximum speed (dba)	65	Sound level maximum speed (Sones)			
Sound level maximum speed/Boost (dba)	69	Sound level maximum speed/Booster (Sones)			
Sound level minimum speed (dba)	50	Sound level minimum speed (Sones)			
Microwave magnetron power	NO	Grill max power (W)	NO		
Suction type	SUCTION AND FILTER				
Dimensions & Weights					
Size	110				
Height PF (mm)	790	Height PF (in)	31 3/32		
Width PF (mm)	998	Width PF (in)	3 15/16		
Depth PF (mm)	450	Depth PF (in)	17 23/32		
Depth with handle (mm)	0	Depth with handle (in)	0		
Depth with open door (mm)	0	Depth with open door (in)	0		
Built-in hole height (mm)	0	Built-in hole height (in)	0		
Built-in hole width (mm)	0	Built-in hole width (in)	0		
Built-in hole depth (mm)	0	Built-in hole depth (in)	0		
Chimney height (mm)	730-1000	Chimney height (in)	28 3/4- 39 3/8		
Package type	WOOD PALLET				
Package height (mm)	1272	Package height (in)			
Package width (mm)	415	Package width (in)			
Package depth (mm)	603	Package depth (in)			
Hood distance from worktop (mm)	500-650	Hood distance from worktop (in)	19 11/16- 25 19/32		
Net weight (Kg)	18.9	Gross weight (Lb)	0.0		
Gross weight (Kg)	22.0	Net weight (Lb)			
Aesthetics					
Badge	SERIGRAPHY	Location of fascia	FRONT		
Handle type	NO	Knob type	NO		
User Interface					
Type of control device	ELECTRIC WITH LED				
Grill power levels	NO	Microwave number of power levels	NO		
General characteristics					
Hood version	WALL MOUNT	Duct cover	INCLUDED		
Duct size diameter (in)		Max height of installation (ft)			
Motor	1	Speed	3 + BOOSTER		
Filter type	STAINLESS STEEL	Filter cleaning	WASHABLE		
Type and number of lights	2 LED				
Filters number	3	Hood Special features			
Perimental aspiration	NO	Digital airflow control	NO		
Microwave					
Microwave type	NO	Microwave functions	NO		
Microwave special features	NO	Turntable	NO		
Cavity material	NO	Light	NO		
Guides type	NO				
Gross volume	0	Net volume	0		
Microwave grill tray	NO	Microwave gasket	NO		
Safety Devices					
Locked controls	NO	Saturation alarm	NO		
Documentation					
Booklet languages	ENGLISH	Warranty certificate	NO		
Miscellaneous					
Marketing remarks					