Product information

- · Indoor use only
- Dimmable When used with dimmable bulbs
- Replacement bulbs should be the same type and rating, available from John Lewis Partners or other established brands
- Clean the fitting with a soft dry cloth. Do not use abrasive chemical cleaners as this will damage the finish



You've switched on the light, but it's not working:

- 1. Check your power supply is switched on
- 2. Turn off the light and check that the bulb is inserted correctly
- 3. Check the bulb is still in working order

If there are technical issues with this product that you can't solve, please contact your nearest John Lewis & Partners shop or call Technical Support on 03301 230106.

Specification

Max power: 3 x 7W Recommended bulb:

7W LED E27 GLS bulb for maximum brightness.

Lower wattages are also suitable. Rated input: 220 –240V, 50Hz

Bulbs not included IP rating: 20 Weight: 2.1kg

5-year guarantee

At John Lewis & Partners we test every light to high quality standards. That means we can offer you a 5-year guarantee.

Recycling

This symbol indicates that this product should not be treated as normal household waste and it should be recycled. John Lewis & Partners do not operate instore take back, but as members of the Distributor Take Back scheme have funded the development and upgrade of recycling facilities across the UK. Please take it to your nearest collection facility or for further details contact your local council or visit www.recycle-more.co.uk.

John Lewis plc SW1V 2QQ johnlewis.com



21/10/2024



Please retain these instructions for future reference.



MILLHOUSE 3 LIGHT CEILING PENDANT USER GUIDE





Product Code: 70159503

Getting started

Thank you for purchasing this John Lewis & Partners product. For your safety, and to make sure everything is working properly, please read the instructions carefully before use.

Warnings

This is a Class II product and must NOT be earthed.

It is recommended that this fitting is installed by a qualified electrician. Install in accordance with the IEE Wiring regulations and the Building Regulations. To prevent electrocution switch off at mains supply before installing or maintaining this fitting. Ensure other persons cannot restore the electrical supply without your knowledge. If you are in any doubt, please consult a qualified electrician.

This light fitting should be connected to a 5 amp fused circuit.

If replacing an existing fitting, make a note of the connections.

Always use the correct type and wattage bulb. Never exceed the wattage stated. Dispose of used bulbs carefully.

This product is suitable for installation on surfaces with normal flammability e.g. wood, plasterboard, masonry. It is not suitable for use on highly flammable surfaces (e.g. polystyrene, textiles).

For your safety, always switch off the supply and allow the fitting to cool down before changing lightbulbs, cleaning or removing shades.

Parts list

Description	Image	Quantity
Light fitting with x 3 shade rings (fitted)		x1
Shades		x 3
Hex key & Spare grub screw		x 1 x 1
		x 2
Screws	(fammanans) (famananas)	x 2

Product assembly

Step 1

Carefully unpack the parts. Remove the two finials (A) from the ceiling cup and detach the mounting plate (B). Set aside. Screw the top of the stem onto the ceiling cup (C) pull any cable up through the ceiling cup. Take care not to twist the cable.

Step 2

Slot the lower stem onto the connector on the bar (D). Once the stem is firmly in, tighten the grub screws using the supplied hex key, to secure the stem (E).

Step 3

Adjust the height of the product by loosening the grub screw (F) and turning the central collar anticlockwise. Carefully push the upper stem down to reduce the height and pull up to increase the height. It will be necessary to pull the cable up into the ceiling cup when adjusting. When the desired height is achieved, retighten the central collar and grub screw to secure the stem. **NOTE:** Do not over-rotate the stem during installation or when in use as damage to the wiring could occur.

Step 4

Using the mounting plate as a template, mark the position of the mounting holes. Taking care to avoid damaging concealed wires and pipes, drill holes and fit supplied wall plugs (G) (suitable for masonry only - for other surfaces use appropriate fixings). Fix the mounting bracket to the ceiling using the supplied screws (H).

Step 5

Having identified the household wiring from your existing light fitting, connect to the connection block (I) inside the product in the following way. Check that: You have correctly identified the house wires. The connections are tight.

No loose strands have been left out of the connection block.

SUPPLY LIGHT FITTING NEUTRAL BLUE (N) SWITCHED LIVE BROWN (L)

Step 6

Refit the product to the mounting plate using the two finials removed in step 1 and tighten to secure. Take care not to trap any wiring.

Step 7

To fit the shades (J), first remove the shade rings (K) from the threaded lampholders. Place the shades over the lampholders and refit the shade rings. Secure in place.

Step 8

Fit the recommended bulbs (L) as per the details overleaf.

Step 9

Replace fuse or circuit breaker and switch on. Your light is now ready for use.

