
This Product Information Sheet has been prepared in accordance with Schedule 8 of S.I. 2021 No. 1095:
The Ecodesign for Energy-Related Products and Energy Information (Lighting Products) Regulations 2021

General Information			
Supplier's name or trade mark:	John Lewis & Partners		
Supplier's address:	171 Victoria Street, London SW1E 5NN		
Model identifier:	70328010		
Type of light source:	LED Lamp		
Lighting technology used:	LED	Non-directional or directional:	DLS
Light source cap-type (or other electric interface)	GU10	Connected light source (CLS):	No
Mains or non-mains:	MLS	Envelope:	SMD
Colour-tuneable light source:	No	High luminance light source:	No
Anti-glare shield:	No	Dimmable:	Yes

General Product Parameters				
Energy consumption in on-mode (kWh/1, 000 h) rounded up to the nearest integer	3W		Energy efficiency class	F
i) Useful luminous flux (Φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	320m		vi) Correlated colour temperature, rounded to the nearest 100K, or the range of correlated colour temperatures, rounded to the nearest 100K, that can be set	3000K
iii) On-mode power (Pon), expressed in W	3.2W		vii) Standby power (Psb), expressed in W and rounded to the second decimal point	0W
viii) Networked standby power (Pnet) for CLS, expressed in W and rounded to the second decimal point	0W		ii) Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80
Outer dimensions without separate control gear, lighting control parts and non-lighting control parts, if any (millimetre)	Height	50mm	Spectral power distribution in the range 250 nm to 800 nm, at full-load	
	Width	18mm		
	Depth	18mm		
Chromaticity coordinates (x and y)	0.315 0.346			
Claim of equivalent power (see paragraph [2(1) and (2)])	No		If yes, equivalent power (W)	N/A

Parameters for directional light sources (DLS)			
v) Peak luminous intensity (cd)	N/A	iv) Beam angle in degrees, or the range of beam angles that can be set	N/A

Parameters for LED and OLED light sources:			
ix) R9 colour rendering index value	22	x) Survival factor	1
xi) The lumen maintenance factor	95%	xii) Indicative lifetime L70B50	No
xiii) Displacement factor (cos φ1)	0.85	xiv) Colour consistency in McAdam ellipses	3.5
xv) luminance-HLLS in cd/mm2 (*only for HLLS*)	N/A	xviii) excitation purity for the colours and dominant wavelength within the given range (*only for CTLS*)	N/A
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage (see paragraph [2 (3)].	No	If yes then replacement claim (W)	N/A
xvi) Flicker metric (Pst LM)	1	xvii) Stroboscopic effect metric (SVM)	0.4