

Specification sheet

In accordance with applicable energy labelling regulations.

NOTE

" * " Asterisk(s) means variant model and can be varied (0-9) or (A-Z).

Samsung			
Model Name		DV9*F09F4S DV9*DB8845**	DV9*DB7845** DV9*DG6845**
Capacity	kg	9.0	9.0
Type		Condenser	Condenser
Energy Efficiency			
A+++ (highest efficiency) to D (least efficient)		A+++	A+++
Energy Consumption			
Annual Energy Consumption (AE_C) (Energy consumption is based on 160 drying cycles of the standard cotton programme at full and partial load, and the consumption of the low-power modes. Actual energy consumption per cycle will depend on how the appliance is used.)	kWh/yr	147.0	147.0
Automatic tumble drier		Yes	Yes
Energy consumption (E_dry) standard cotton programme at full load	kWh	1.20	1.20
Energy consumption (E_dry.1/2) standard cotton programme at partial load	kWh	0.66	0.66
off mode and left-on mode			
The power consumption off-mode (P_o) at full load	W	0.50	0.50
The power consumption in left-on mode (P_l) at full load	W	5.00	5.00
Duration of the left-on mode	min	10	10
Programme to which the information on the label and the Sheet relate ('standard cotton programme' used at full and partial load is the standard drying programme to which the information in the label and the fiche relates. This programme is suitable for drying normal wet cotton laundry and it is the most efficient programme in terms of energy consumption for cotton. Consumption data can vary from the nominal values given above depending on the size of the load, types of textiles, residual moisture levels after spinning, fluctuations in the electricity supply and any extra options selected.)	Eco Cotton + Dry Level 3 + (Wrinkle Prevent Off)		
programme duration of the standard program			
Weighted Programme time standard cotton programme at full load and partial load	min	214	214
Programme Time (T_dry) standard cotton programme at full load	min	285	285
Programme Time (T_dry.1/2) standard cotton programme at partial load	min	160	160
condensation efficiency class			
A (most efficient) to G (least efficient)		B	B
Average condensation efficiency at full load	%	88	88
Average condensation efficiency at partial load	%	88	88
Weighted condensation efficiency	%	88	88
Airborne noise emissions			
Dry at full load	dB (A) re 1 pW	62	65