

Type	Technical Code	Commercial Code	Code		
Hoods	K21BNLF1DEB00	KPH120MASNET	F005336		
General Information					
Stato	Released	Life Cycle	Y2 - On Management		
Product family	HOODS WALLMOUNT 60-120 CM	Aesthetical line	MASTER	Colour leading code	MATT BLACK
Brand	BERTAZZONI	Private Label	BERTAZZONI		
Make or Buy Flag	Bought	Type of production	CBU		
Type of installation	FREE STANDING	Factory	Guastalla		
Technical code	K21BNLF1DEB00	Predecessor Code		Technical code of derivation	
Commercial description	120cm Master Chimney Hood	Short Description FR Short Description US Ean code	Maitre de hotte de cheminée 120cm 120cm Master Chimney Hood 8059304886683		
Short Description IT	120cm Master Chimney Hood				
Short Description EN	120cm Master Chimney Hood				
EAN Required	YES	Second commercial code			
Commercial code	KPH120MASNET	Customer	GENERICO		
Market	EUROPE	Approvals	CE	Approval code	
Years of warranty		Changes notes			
Notes					
Energy Label					
Energy Label Required	YES	Annual energy consumption - AEEhood (kWh/annum)	49.9		
Fluid dynamic efficiency class	A	Fluid dynamic efficiency	31.3		
Energy efficiency class	A				
Measured air pressure at best efficiency point - Pbepp (Pa)	389	Minimum air flow in normal use (m³/h)	322.0		
Maximum air flow in normal use (Intensive / Boost Excluded) (m³/h)	603	Air flow at Intensive/Boost Setting - (m³/h)	740.0		
Lighting efficiency class	C	Light efficiency	16.3		
Power consumption in standby mode - Ps (W)	0.49	Power consumption off Mode - Po (W)			
Grease filtering efficiency - GFEhood (%)	32.5	Grease filtering efficiency class	G		
Energy Label Country	UE + UK				
Technical Data					
Supply voltage [V]/Supply frequency [Hz]	220-240 V, 50/60 HZ	Absorbed power [W]	258		
Absorbed current [A]	1	Plug type	NO		
Minimum Cable length (m)	1.3	Minimum Cable length (in)	51"		
Output air extraction (m³/h)	740				
Max extraction power (CFM)	NON APPLICABLE	Max extraction power (SONES)			
Sound level maximum speed (dba)	61	Sound level maximum speed (Sones)			
Sound level maximum speed/Boost (dba)	66	Sound level maximum speed/Booster (Sones)			
Sound level minimum speed (dba)	47	Sound level minimum speed (Sones)			
Microwave magnetron power	NO	Grill max power (W)	NO		
Suction type	SUCTION AND FILTER				
Dimensions & Weights					
Size	120	Height PF (in)			
Height PF (mm)	450	Width PF (in)			
Width PF (mm)	1158	Depth PF (in)			
Depth PF (mm)	500	Depth with handle (in)			
Depth with handle (mm)		Depth with open door (in)			
Depth with open door (mm)					
Built-in hole height (mm)		Built-in hole height (in)			
Built-in hole width (mm)		Built-in hole width (in)			
Built-in hole depth (mm)		Built-in hole depth (in)			
Chimney height (mm)	525-845	Chimney height (in)			
Package type	STANDARD PACKING				
Package height (mm)	625	Package height (in)			
Package width (mm)	1290	Package width (in)			
Package depth (mm)	890	Package depth (in)			
Hood distance from worktop (mm)		Hood distance from worktop (in)			
Net weight (Kg)	30	Gross weight (Lb)	0.0		
Gross weight (Kg)	41.0	Net weight (Lb)			
Aesthetics					
Badge	SERIGRAPHY	Location of fascia	FRONT		
Handle type	NO	Knob type	NO		
User Interface					
Type of control device	ELECTRIC WITH LED				
Grill power levels	NO	Microwave number of power levels	NO		
General characteristics					
Hood version	WALL MOUNT	Duct cover	INCLUDED		
Duct size diameter (in)		Max height of installation (ft)			
Motor	1	Speed	3 + BOOSTER		
Filter type	BAFFLE STAINLESS STEEL	Filter cleaning	WASHABLE		
Type and number of lights	LED BAR				
Filters number	4	Hood Special features	24H FUNCTION;TIMER		
Perimental aspiration	NO	Digital airflow control	NO		
Microwave					
Microwave type	NO	Microwave functions	NO		
Microwave special features		Turntable	NO		
Cavity material	NO	Light	NO		
Guides type	NO				
Gross volume	0	Net volume	0		
Microwave grill tray	NO	Microwave gasket	NO		
Safety Devices					
Locked controls	NO	Saturation alarm	YES		
Documentation					
Booklet languages	DANISH;DUTCH;ENGLISH;FRENCH;ITALIAN;SPANISH;SWEDISH	Warranty certificate	NO		
Miscellaneous					
Marketing remarks					