


This Product Information Sheet has been prepared in accordance with Schedule 8 of S.I. 2021 No. 1095: The Ecodesign for Energy-Related Products and Energy Information (Lighting Products) Regulations 2021				
General Information				
Supplier's name or trade mark:		John Lewis & Partners		
Supplier's address:		171 Victoria Street, London SW1E 5NN		
Model identifier:		76651716		
Type of light source:				
Lighting technology used:		LED	Non-directional or directional:	Non-directional
Light source cap-type (or other electric interface)		NON-standard	Connected light source (CLS):	NO
Mains or non-mains:		non-mains	Envelope:	NO
Colour-tuneable light source:		NO	High luminance light source:	NO
Anti-glare shield:		NO	Dimmable:	NO
General Product Parameters				
Energy consumption in on-mode (kWh/1,000 h) rounded up to the nearest integer		3	Energy efficiency class	G
i) Useful luminous flux (Φ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		183	vi) Correlated colour temperature, rounded to the nearest 100K, or the range of correlated colour temperatures, rounded to the nearest 100K, that can be set	2752
iii) On-mode power (P_{on}), expressed in W		3.3	vii) Standby power (P_{sb}), expressed in W and rounded to the second decimal point	0.5
viii) Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal point		x.xx	ii) Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	63
Outer dimensions without separate control gear, lighting control parts and non-lighting control parts, if any (millimetre)		Height	173	Spectral power distribution in the range 250 nm to 800 nm, at full-load
		Width	192	
		Depth	94	
Chromaticity coordinates (x and y)		x:0.456 y:0.410		
Claim of equivalent power (see paragraph [2(1) and (2)])		[yes/-]	If yes, equivalent power (W)	x
Parameters for directional light sources (DLS)				
v) Peak luminous intensity (cd)		x	iv) Beam angle in degrees, or the range of beam angles that can be set	[x/x...x]
Parameters for LED and OLED light sources:				
ix) R9 colour rendering index value		-62	x) Survival factor	1
xi) The lumen maintenance factor		0.7	xii) Indicative lifetime L70B50	3600hrs
xiii) Displacement factor ($\cos \varphi_1$)		x.xx	xiv) Colour consistency in MacAdam ellipses	1.2
xv) luminance-HLLS in cd/mm2 (only for HLLS)		x	xviii) excitation purity for the colours and dominant wavelength within the given range (only for CTLS)	Blue 440nm - 490nm Green 520nm - 570nm Red 610nm - 670nm
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage (see paragraph [2(3)]).		[yes/-]	If yes then replacement claim (W)	x
xvi) Flicker metric (Pst LM)		x.x	xvii) Stroboscopic effect metric (SVM)	x.x