


General Information			
Supplier's name or trade mark:	John Lewis & Partners		
Supplier's address:	1 Drummond Gate, Pimlico, London, SW1V 2QQ		
Model identifier:	70146403		
Type of light source:	LED tape module		
Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type (or other electric interface)	SMD	Connected light source (CLS):	No
Mains or non-mains:	NMLS	Envelope:	No
Colour-tunable light source:	No	High luminance light source:	No
Anti-glare shield:	No	Dimmable:	Yes

General Product Parameters			
Energy consumption in on-mode (kWh/l, 000 h) rounded up to the nearest integer	29W		Energy efficiency class
			E
i) Useful luminous flux (Φ _{use}) indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	1500 lm (integrating sphere)		vi) Correlated colour temperature, rounded to the nearest 100K, or the range of correlated colour temperatures, rounded to the nearest 100K, that can be set
			3000K
iii) On-mode power (P _{on}), expressed in W	28.5W		vii) Standby power (P _{sb}), expressed in W and rounded to the second decimal point
			0W
viii) Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal point	0.45W		ii) Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set
			80
Outer dimensions without separate control gear, lighting control parts and non-lighting control parts, if any (millimetre)	Height	1900mm	Spectral power distribution in the range 250 nm to 800 nm, at full-load
	Width	1200mm	
	Depth	85mm	
Chromaticity coordinates (x and y)	0.463 0.406		
Claim of equivalent power (see paragraph [2(1) and (2)])	No		If yes, equivalent power (W)
			N/A

Parameters for directional light sources (DLS)			
v) Peak luminous intensity (cd)	No		iv) Beam angle in degrees, or the range of beam angles that can be set
			No

Parameters for LED and OLED light sources:			
ix) R9 colour rendering index value	8		x) Survival factor
			1
xi) The lumen maintenance factor	96%		xii) Indicative lifetime L70B50
			30,000hrs
xiii) Displacement factor ($\cos \phi_1$)	>0.95		xiv) Colour consistency in McAdam ellipses
			6
xv) luminance-HLLS in cd/mm ² (only for HLLS)	No		xviii) excitation purity for the colours and dominant wavelength within the given range (only for CTLS)
			No
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage (see paragraph [2 (3)]).	No		If yes then replacement claim (W)
xvi) Flicker metric (Pst LM)	0.2		xvii) Stroboscopic effect metric (SVM)
			0.1