Data sheet for household cooker hoods
In acc. with delegated regulation (EU) No. 65/2014 and regulation (EU) No. 66/2014

Miele				
Model name / identifier		PUR 68 W		
Annual Energy Consumption (AEC)				
(AEC _{rpm})	kWh/year	47,0		
Energy efficiency class		Α		
Energy efficiency index (EEI) (EEI _{mm})		48,4		
Fluid Dynamic Efficiency (FDE) (FDE _{mm})		32,8		
Fluid Dynamic Efficiency class		- /-		
A (most efficient) to G (least efficient)		Α		
Lighting Efficiency (LE) (LE _{rpm})	lx/W	55,0		
Lighting Efficiency class				
A (most efficient) to G (least efficient)		Α		
Grease Filtering Efficiency	%	95,1		
Grease Filtering Efficiency class				
A (most efficient) to G (least efficient)		Α		
Airflow at best efficiency point	m³/h	374,5		
Air flow (min. speed)	m³/h	265		
Air flow (max. speed)	m³/h	395		
Air flow (intensive or boost setting)	m³/h	650		
Max. air flow (Q) (Q _{max})	m³/h	650		
Air pressure at best efficiency point	Pa	450		
Airborne acoustical A-weighted sound power emis	sions			
(min. speed)	dB	47		
Airborne acoustical A-weighted sound power emis				
(max. speed)	dB	56		
Airborne acoustical A-weighted sound power emis				
(intensive or boost setting)	dB	67		
Electrical power input at best efficiency point	W	142,7		
Power consumption in off mode (P _o)	W			
Power consumption in standby mode (Ps)	W	0,20		
Nominal power of lighting system	W	6,0		
Average illumination of the lighting system on the	cooking lx	330		
surface Time increase factor	IX	330 0,8		
Time increase factor		0,8		