

Care instructions

We recommend cleaning with a soft dry cloth. Do not use abrasive materials as these will damage the finish.

Recommended bulb

3 x 3 Watt energy efficient LED

This product contains a non-replaceable LED Module. If the LEDs become damaged then the whole product must be replaced.

When moving or cleaning, always switch off at the mains and allow the module to cool before handling.

Specifications

Max. power: 3x 3W

Voltage: 240V, 50Hz

IP rating: IP44

Weight: 1.4kg


750 lumen output

Colour temperature: Warm white (3000K)



Please retain these instructions for future reference.



This symbol  indicates that this product should not be treated as normal household waste and it should be recycled. John Lewis do not operate instore take back, but as members of the Distributor Trade Back scheme have funded the development and upgrade of recycling facilities across the UK. Please take it to your nearest collection facility or for further details contact your local council or visit www.recycle-more.co.uk.

We have taken great care to ensure that this product reaches you in perfect condition. However, should any parts be damaged or missing please contact the Product Helpline on (01202) 690945.

John Lewis Partnership
171 Victoria Street
London SW1E 5NN
johnlewis.com


Made in China

John Lewis

User manual

Oslo

Spotlight



18/04/2018

Thank you for purchasing this Oslo spotlight. Please read the instructions carefully before use to ensure safe and satisfactory operation of this product.

Warnings!

This is a Class II product and must **NOT** be earthed.

Please read these instructions carefully before commencing any work.

It is recommended that this fitting is installed by a qualified electrician.

Install in accordance with the IEE Wiring regulations and the Building Regulations.

To prevent electric shock switch off at mains supply before installing or maintaining this fitting.

Ensure other persons cannot restore the electrical supply without your knowledge.

If you are in any doubt, please consult a qualified electrician.


This light fitting should be connected to a 5 amp fused circuit.

If replacing an existing fitting, make a note of the connections.


This product is suitable for installation on surfaces with normal flammability e.g. wood, plasterboard, masonry. It is not suitable for use on highly flammable surfaces (e.g. polystyrene, textiles).

Ensure the correct fixings are used for the installation surface.





For your safety, always switch off the supply before cleaning or adjusting the fitting.



This product has special protection against the ingress of moisture and is IP44 rated. This product is suitable for use in Zone 1, Zone 2, and outside Zones of a bathroom. See diagram. **If installing in a bathroom a 30mA RCD must be used in accordance with IEE Wiring Regulations and the Building Regulations.**

 The shades must be replaced if they become cracked or damaged. Do not use product without shades attached.

Parts list


Parts list	Image	Qty
Light fitting		1
Screws		2
Wall plugs		2
Acrylic shade		3

Assembly

Refer to assembly drawings. Carefully unpack the carton, making sure all the parts are present before assembly.

Step 1


Before removing the existing fitting, **carefully note the position of each set of wires.**



Step 2


Remove the protective cover from the LED modules. Screw on the acrylic shade.

Figure 2



Step 3

Remove the fixing bracket (A) from the ceiling cover by removing the side screws (B). See Fig. 2.




Step 4

Attach to the ceiling using the screws provided. Refer to Fig. 3. Ensure there is a joist at the point of fixing to support the weight of the product. Take care to avoid damaging any concealed wiring and pipes.

Step 5

Having identified the household wiring from your existing light fitting, connect to the connection block inside the product as shown. When completed, ensure that there are no bare or loose strands of wire exposed, and cover all exposed areas of the connection block with 2 layers of insulation tape.



Check that

You have correctly identified the house wires.

The connections are tight.

No loose strands have been left out of the connection block.

Step 6

Referring back to Figure 2, reattach the product to the fixing strap. This product has "L" shaped fixing slots to allow easy fixing to the ceiling strap. Locate the "L" slots (C) around the small screws (B) on the ceiling strap (A). Rotate the ceiling cover to attach the product to the strap. Tighten the screws to secure. Take care not to trap any wiring.

Step 7

Replace fuse or circuit breaker and switch on. Your light is now ready for use.