product information sheet

Trade Mark	AEG	
Model	DBE5661HG 942051331	
Annual Energy Consumption (kWh/year)	52.9	
Energy Efficiency class	A	
Fluid Dynamic Efficiency	30.5	
Fluid Dynamic Efficiency class	Α	
Lighting Efficiency (lux/W)	45.3623188405797	
Lighting Efficiency class	А	
Grease Filtering Efficiency	85.1	
Grease Filtering Efficiency class	В	
Air flow at minimum and maximum speed in normal use (m3/h)	285/400	
Air flow at intensive or boost setting (m3/h)	700	
Airborne acoustical A-weighted sound power emissions at minimum and maximum speed in normal use (dB(A))	44/54	
Airborne acoustical A-weighted sound power emissions at intensive or boost setting (dB(A))	65	
Power consumption in standby mode (W)	0	
Power consumption in off mode (W)	0.49	

Product information according to Commission regulation (EU) No 66/2014

Attribute Name	Symbol	Value	Unit
Model Denomination		DBE5661HG 942051331	
Annual Energy Consumption	AEChood	52.9	kwh/a
Time increase factor	f	0.9	
Fluid Dynamic Efficiency	FDEhood	30.5	
Energy Efficiency Index	EEIhood	53.3	
Measured air flow rate at best efficiency point	QBEP	375.9	m3/h
Measured air pressure at best efficiency point	Рвер	426	Pa
Maximum air flow	Qmax	700,0	m3/h
Measured electric power input at best efficiency point	WBEP	145.8	W
Nominal power of the lighting system	WL	6.9	W
Average illumination of the lighting system on the cooking surface	Emiddle	313	lux
Measured power consumption in standby mode	Ps	0	W
Measured power consumption off mode	Po	0.49	W
Sound power level	Lwa	54	dB

EN 60704-2-13 - Household and similar electrical appliances – Test code for the determination of airborne acoustical noise – Part 2-13: Particular requirements for range hoods

EN 50564 - Electrical and electronic household and office equipment. Measurement of low power consumption

Suggestions for a correct use in order to reduce the environmental impact:

- Switch ON the hood at minimum speed when you start cooking and kept it running for few minutes after cooking is fi nished.
- Increase the speed only in case of large amount of smoke and vapour and use boost speed(s) only in extreme situations.
- Replace the charcoal filter(s) when necessary to maintain a good odour reduction effi ciency.
- Clean the grease filter(s) when necessary to maintain a good grease filter efficiency.
- Use the maximum diameter of the ducting system indicated in this manual to optimize effi ciency and minimize noise.