

Product Information Sheet (EU Regulation 2019/2013)

Parameter		Parameter or Value and Precision		Unit	
1	Supplier's name or trade mark	Panasonic			
	Supplier's address	Panasonic Testing Centre Panasonic Marketing Europe GmbH Winsbergring 15, 22525 Hamburg, Germany			
2	Model identifier	TX-55LXW834 TX-55LX800B TX-55LX800E TX-55LX810E TX-55LX820E TX-55LXT886 TX-55LXF887 TX-55LXN888 TX-55LXX889			
3	Energy efficiency class for Standard Dynamic Range (SDR)	G			
4	On mode power demand for Standard Dynamic Range (SDR)	84,0		W	
5	Energy efficiency class (HDR)	G			
6	On mode power demand in High Dynamic Range (HDR) mode, if implemented	174		W	
7	Off mode, power demand, if applicable	0,3		W	
8	Standby mode power demand, if applicable	0,5		W	
9	Networked Standby mode power demand, if applicable	2,0		W	
10	Electronic display category	Television			
		Monitor			
		Signage			
		Other			
11	Size ratio	16	:	9	integer
12	Screen resolution (pixels)	3840	x	2160	pixels
13	Screen diagonal	139		cm	
14	Screen diagonal	55		inches	
15	Visible screen area	82,30		dm ²	
16	Panel technology used	LED LCD			
17	Automatic Brightness Control (ABC) available	YES			
		NO			
18	Voice recognition sensor available	YES			
		NO			
19	Room presence sensor available	YES			
		NO			
20	Image refresh frequency rate (default)	50		Hz	
21	Minimum guaranteed availability of software and firmware updates (from the date of end of the placement on the market)	8		Year	
22	Minimum guaranteed availability of spare parts (from the date of end of the placement on the market)	7		Year	
23	Minimum guaranteed product support	7		Year	
	Minimum duration of the general guarantee offered by the supplier	1		Year	
24	Power supply type	Internal			
		External			
		Standardised external			
25	External power supply (non standardized and included in the product box)				
i					
ii		Input Voltage		V	
iii		Output Voltage		V	
26	External standardised power supply (or suitable one if not included in the product box)				
i		Standard Name or list			
ii		Required output voltage		V	
iii		Required delivered current		A	
iv		Required current frequency		Hz	